



Single Port Dual Fiber Gigabit PoE Media Converter (G-MC-MMDFSC)

Single Port Dual Fiber Gigabit Media Converter



- ◆100/1000M multimode dual fiber media converter
- ◆Card-type or Stand-alone type for your choice
- ◆Broadcasting filtration function, automatic recognizing and modifying address with store-and-transmission operational mechanism
- ◆Ethernet 10base-t or 100Base-TX 100Base-FX fiber media transmission
- ◆Compatible with IEEE802.3, IEEE802.3U, IEEE802.3X, IEEE 802.3z/AB, IEEE802.1d standard
- ◆The electrical interface port supports 1000Mbps, 100Mbps, 10Mbps, both ends can use different speed (full-duplex work bandwidth for line-speed 2XMbps)

Product Description

This 100/1000M media converter can be used between 10Base-T and 10Base-FL or 100Base-TX cable and 100Base-FX fiber cable or 1000Base-T cable and 1000Base-S/LX fiber cable for data transmission. It provides stand-alone RJ-45 electrical interface port and supply power to others, and can automatically cross connection with switch and hub network. And feature with link loss diagnosis, electrical port link diagnosis and optical port link diagnosis, dynamic data transmission, full-duplex/half-duplex, speed indicator. Also it can realize the interconnection between motherboard servers, Repeaters, hubs, switches terminal.


Plug and play design makes easy installation, no on-site adjustment, all the light, electrical interface port is in line with international standards. It can extend the network transmission up to 20km. This gigabit fiber media converter is suitable for Bad industrial environment or high requirements for lightning protection, Intelligent transportation supervisory system (ITS) and safe city, High-speed way supervisory/Tele-communication system, IP network camera, security surveillance system for large corporations, multi-function network system.



Technical Specification


Product Name	Single Port Dual Fiber Gigabit Media Converter
Product Model	G-MC-MMDFSC
Interface	1x copper cable RJ45 port +1x fiber SC port, support power supply
Transmission Distance	500Km
Fiber Description	Multimode dual fiber, SC port
Fiber Bandwidth	1.25G
Wavelength	850nm
Network Bandwidth	1000MHz
Ethernet Specifications	Bandwidth: 1.6Gbps (non-blocking) Network Latency (100 to 100Mbps): the maximum delay less than 20 microseconds Packet Buffer Memory: 96KB Address Database Size: 1,000 MTBF: 100,000 hours
Protocol	IEEE 802.3i 10BASET IEEE 802.3u 100BASETX IEEE 802.3x Flow Control IEEE 802.3af DTE Power via MDI
LED Indicator	System, Power, Connecting , working status
Power Supply	3.5W
Dimension/ Weight	Dimension : 116×99×25.5mm Weight : 0.65kg
Working Environment	Working Temperature: 0°~ 55°C Storage Temperature: -20°~ 75°C Working Humidity: 10%~90%, non-condensing Storage Humidity: 10%~95%, non-condensing Operational Altitude: 3000m (10,000ft) Storage Altitude: 3000m (10,000ft)
Radiation	CE mark, commercial FCC Part 15 Class B VCCI Class B EN 55022 (CISPR 22), Class B
Safety	CE mark, commercial CE/LVD EN60950
Warranty	1 year warranty (2 years warranty for power adapter)

Dimension



A. 155M Uplink Port B. 100/1000M RJ45 Port C. Power Input Port-DC5V

Product Display





Product Packing Lists

Package List	Single Port Dual Fiber Gigabit Media Converter (G-MC-MMDFSC)
	Power Adapter
	User Guide
	Warranty Card