

CYBOX AP 2-W

Industrial and Mobile IEEE 802.11ac Dual Radio

Wireless Access Point

- Designed for harsh Industrial and Mobile Applications
- EN 50155 Compliant
- Wall Mount Solution

III Main Features

- IEEE802.11ac compliant with up to 2.600 Mbps
- Backwards compatible with 802.11a/b/g/n
- Simultaneous operation on 2.4 GHz and 5 GHz frequencies possible
- Dual Core CPU @ 1.200 MHz
- Wide range power supply 24 – 110 VDC
- Designed for harsh industrial and mobile applications
- -40 to +70 °C operating temperature
- EN 50155 compliant
- Integrated firmware for management and configuration

III Description

The CyBox AP 2-W is a member of the CyBox family of robust industrial Ethernet access points for wall mounting. It is particularly designed to meet requirements of rolling stock and automotive applications. With the assistance of the access point, multiple mobile WLAN compatible devices in a passenger train, long distance bus or subway have the possibility to communicate with the Internet or access local data, such as time table information, videos, etc. The built-in configurable firewall ensures that mobile clients cannot gain access to other clients in the WLAN. Another important use case is the construction of wireless network backbones in train retrofit programs.

In the CyBox AP 2-W a QorIQ of the latest generation is used. This provides sufficient power reserves even with an evolution of WLAN standards to achieve enough throughput. The SoC has two independent Gigabit-Ethernet-MACs, both connected to robust M12 sockets. Thus, for very flexible uplink configurations to the point of Redundancy structures or link aggregation to increase the uplink-bandwidth. In daisy chaining, the bypass relays (as an option) are very useful between the Ethernet ports, because when switching off the access point subsequent devices can still be achieved.

The CyBox AP 2-W supports maximum data rates in current and future versions of IEEE802.11ac standards. Therefore, optionally, a Version with a 2.5-Gigabit Ethernet interface and a version with 10 Gigabit optical interface will be available. While the first option is for retrofit programs with existing cabling (CAT 6 or better), the optical variant addressed predominantly new infrastructure.

Mechanically and electrically the CyBox AP 2-W is compatible with its predecessors, so that a migration in existing programs is easily possible.

The CyBox AP 2-W hosts two independent WLAN radios, allowing operation of flexible wireless network configurations, including different frequency bands. The WLAN interfaces are fully compliant to IEEE 802.11ac, allowing to connect clients at high data rates up to 1.3 Gbps on each interface.

The CyBox AP 2-W provides very flexible powering options. It can be supplied by a local 24 to 110 VDC power source; the power input supply is fully compliant to EN 50155, Class S2 and tolerates an input voltage range from 16.8 to 154 V as well as power interruptions up to 10 ms. As a second source of supply the CyBox AP 2-W provides an IEEE802.3at compliant PoE input for Class 4 powered device mode. Its capability to supply power to a second CyBox

AP 2-W, if it is connected to the downlink port is a unique feature. This setup allows supplying two access points over PoE and providing extended wireless illumination using just one CAT-X cable; a noticeable cost saving factor especially in retrofit programs.

The robust IP40 aluminium housing can be deployed in industrial and mobile environments; it does not require forced air cooling in temperature ranges between -40 and +70 °C (EN 50155, Class TX) and has no maintainable parts inside. The housing is especially suited for use in rugged environments with regard to shock and vibration according to applicable DIN, EN or IEC industry standards. Its electrical and mechanical robustness is supported by industry standard M12 connectors for Ethernet, and QLS connectors for the RF interfaces.

The CyBox AP 2-W firmware provides a comfortable management interface through http service. Besides global setup parameters the software allows complete configuration of the WLAN interfaces, such as channel selection, SSID, encryption keys, and firewall setup. Access point configurations can be up- and downloaded and the complete management firmware can be upgraded.

The CyBox AP 2-W provides the possibility to read its configuration data from a USB memory device that can be attached via M12 connector; a prerequisite for quick and easy installation in the field.

A unique feature of the firmware is provided with the Inter Carriage Connection Protocol, which resembles a bridging algorithm that has been developed by ELTEC to automatically establish and maintain a wireless LAN backbone for trains. Such wireless backbones can be used in retrofit applications, where there is no possibility to add Ethernet cables through the car coupling. The challenge is to establish and maintain such connections in an environment, which is unstable and exposed to external sources of disturbances, such as train re-configuration, connection losses, or other trains on neighbour tracks.



III Standards and Specifications

Standards

- IEEE 802.11a/b/g/n/ac for Wireless LAN
- IEEE 802.11i for Wireless Security
- IEEE 802.3 for 10BaseT
- IEEE 802.3u 100BaseTX and 100Base FX
- IEEE 802.3ab for 1000BaseT
- IEEE 802.3af for Power-over-Ethernet IEEE 802.3af
- IEEE 802.1Q VLAN

EMC (RED - 2014/53/EU)

Tested according to the following railway standards:

- EN 55011 (radio disturbance)
- EN 50121-3-2 (EMC)
- EN 61000-4-2 (ESD)
- EN 61000-4-3 (electromagnetic field immunity)
- EN 61000-4-4 (burst)
- EN 61000-4-5 (surge)

WLAN and LTE radios compliant to:

- ETSI EN 300 328
- ETSI EN 301 893
- ETSI EN 301 502
- ETSI EN 301 489-1
- ETSI EN 301 489-17
- ETSI EN 60950-1
- ETSI EN 62311

Safety

Flammability: compliant to

- EN 45545 (HL 1 to HL 4)
- DIN 5510 (1 to 4) for use in technical cabinets
- BS6853 & GM/RT2130, categories II, Ib Ia, A, B, OC1, OC2, OC3 and OC4
- NFF 16 102, categories B, A2 and A1

WLAN Interfaces (Complex WLE900VX-I Radios)

RF	3 RF signal inputs, 3T3R MIMO technology
Operating Frequency	11b/g/n ISM band: 2.400 ~ 2.4835 GHz 11a/ac ISM band: 5.180 GHz ~ 5.825 GHz
Transmission Rates	802.11b: 1, 2, 5.5, 11 Mbps 802.11a/g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps 802.11n: 6.5 to 450 Mbps 802.11ac: up to 1300 Mbps
Output Power	802.11a: 17 dBm ± 2 dBm @ 54 Mbps 802.11b: 21 dBm ± 2 dBm @ 11 Mbps 802.11g: 18 dBm ± 2 dBm @ 54 Mbps 802.11gn HT20: 16 dBm ± 2 dBm @ MCS7 802.11gn HT40: 16 dBm ± 2 dBm @ MCS7 802.11an/ac HT20: 16 dBm ± 2 dBm @ MCS7 802.11an/ac HT40: 15 dBm ± 2 dBm @ MCS7 802.11ac HT80: 15 dBm ± 2 dBm @ MCS7
Receive Sensitivity	802.11a: -80 dBm ± 2 dBm @ 54 Mbps 802.11b: -94 dBm ± 2 dBm @ 11 Mbps 802.11g: -80 dBm ± 2 dBm @ 54 Mbps 802.11gn HT20: -77 dBm ± 2 dBm @ MCS7 802.11gn HT40: -75 dBm ± 2 dBm @ MCS7 802.11an/ac HT20: -75 dBm ± 2 dBm @ MCS7 802.11an/ac HT40: -75 dBm ± 2 dBm @ MCS7 802.11ac HT80: -72 dBm ± 2 dBm @ MCS7
Encryption	AES, TKIP, WEP
Security	Visible / invisible SSID 64-bit and 128-bit WEP encryption, WPA / WPA2-personal and enterprise Firewall

III Technical Data

Physical Interfaces

Antenna	QLS connectors
LAN	2x 10/100/1000BaseT(X), M12 X-coded
USB Port	M12, X-coded
Power Input	24 to 110 VDC local supply on M12 A-coded, PoE
LED Indicators	Power, Fault, LAN 1, LAN 2, WLAN 1, WLAN 2
Reset Switch	Available on the front cover (access protected)

Mechanical Specifications

Dimensions: 105 mm x 55 mm x 205.2 mm
Weight: 1100 g
Aluminium IP40 housing, prepared for wall-mounting

Electrical Specifications

Local supply voltage: 24 to 110 VDC nominal (14,4 V min to 154 V max.),
Compliant to EN 50155, Class S2, or PoE, Class 4 powered device according to IEEE 802.3at
Power consumption: ~15 W typ., ~20 W max.

Environmental Conditions

Temperature range (operation): -40..+70 °C (+85 °C for 10 min., according to EN 50155, Class TX)
Temperature range (storage): -40..+85 °C
Relative humidity (operation): max. 90 % non-condensing
Relative humidity (storage): max. 90 % non-condensing
Altitude: -300 m to + 2000 m
Climatic tests according to EN 68068
Shock and vibration tested according to EN 61373, Category 1, Class B
Conformal coating

MTBF

→ Approx. ~260000h



Standard Configurations

Article No.	Description
CYAPW-1050Vo	2x WLAN Radio, 2x 1 Gbit Eth MACs
CYAPW-1053Vo	2x WLAN Radio, 2x 1 Gbit Eth MACs, Bypass Relays
CYAPW-1054Vo	2x WLAN Radio, 1x 1 Gbit Eth & 1x 2.5 Gbit Eth
CYAPW-1055Vo	2x WLAN Radio, 1x 1 Gbit Eth & 1x 10 Gbit Eth (optical)
CYAPW-1061Vo	2x WLAN Radio, 2x 1 Gbit Eth MACs, Switch
CYAPW-1062Vo	2x WLAN Radio, 2x 1 Gbit Eth MACs, Switch, Bypass Relays

Options

→ SMA antenna connectors

Accessories

→ DIN-rail mounting plate

Related Products

- CyBox AP-R – Wireless Access Point for rack mounting
- CyBox LTE 2-W – LTE Router for wall mounting

ELTEC Elektronik AG

Galileo-Galilei-Str. 11
55129 Mainz

PO Box 10 03 64
55134 Mainz

Germany

Fon +49 6131 918 100
Fax +49 6131 918 195

Email info@eltec.com
www eltec.com

Copyright © 2017 by ELTEC Elektronik AG, Mainz. All rights reserved. The information in this document has been carefully checked and is believed to be entirely reliable. However, no responsibility is assumed for inaccuracies. Furthermore, ELTEC reserves the right to make changes to any products herein to improve

reliability, function or design. ELTEC does not assume any liability arising out of the application or use of any product or circuit described herein; neither does it convey any license under its rights or the right of others. All trademarks are the property of their owners. Printed in Germany.

Revision: 8.0 | Date: 07.09.2018 | Name: AFr